

# DEFED

Strong Defender to simplify your home security



2020.10





### Door/Window Sensor

A narrow design opening contact, applicable for any windows or doors you want. The built-in temperature sensor could make users aware of room environment.









Long Distance Signal Transport via CoSS

Tamper Protection Suitable For Any Door Or Window Battery Life Up Te 10 Years



#### Wall-mount Bracket $\diamond$

Fixed to the wall by 3M adhesive or screws. Prevents the sensor from being violently removed off the wall.

#### Physical Power On/Off Switch $\diamond$

Easy to turn on/off the sensor, not bothering to take down and plug in battery



### CoSS<sup>™</sup> Wireless Transmission Technology

- **Stable Connections:** Designed with High-frequency heartbeat mechanism, in case of power loss, contact loss or other problems, the connection failure can be detected within less than 40s.
- Ultra Power-saving: The power consumption can be dynamically adjusted according to the distance between the sensor and Smart Station to optimize the power consumption.
- Never Loss of Signal: Thanks to the two-way communication mode, the Smart Station will return a feedback to the sensor when receive an alarm signal. In case of time-out feedback, the sensor will send the alarm signal repeatedly to ensure the robustness of transmission.



# Intrusion Protection

Send alarm notifications to you via LifeSmart when someone intrudes illegally. And the DEFED Siren worked in the alarm system will produce sound alarm to deter the intruder.

#### 

# **Tamper Protection**

If someone violently removes the DEFED Door/Window sensor off the wall, you will get notifications via LifeSmart app and you can restore your IoT alarm system in the first place.

#### Never forget to close the Windows

Together with LifeSmart AI Builder, it can send a closing reminder to you as the window is open before you leave home every day. No matter it's windy or rainy, there's no need to worry about any damage or lost in your room.

#### Welcome Home

You can set smart scenes for DEFED Door/Window sensor to automatically light up when you back home during certain periods.





#### New usage for your old sensors

Every DEFED Door/Window can connect an extended sensor via NC interface. So you can add the suitable traditional sensor, for example a sensor used for the shutter, to the new smart home and alarm system.





### Temperature Detection for Smart Heating CA

DEFED Door/Window can detect your room temperature. The smart heating equipments in LifeSmart system could adjust automatically according to your room temperature.





#### HomeKit Apple HomeKit



Works with Apple HomeKit when added to Smart Station. The Home app will notify you when the door sensor is closed or opened. On that basis, you can set scenes to be triggered by the door's switch.







#### Compact size to be applied to thousands of scenarios



# **Guard Dangerous Goods**

For the important or dangerous cabinet, DEFED Door/Window

Sensor can also be used to prevent them from being touched

or removed by kids or pets.

## Keep Your Family Member Safe

Remotely monitor to keep the elderly, children, or pets safe from danger.

#### Spec

| General |
|---------|
|---------|

| Model Number          | LS202WH                          |
|-----------------------|----------------------------------|
| Installation          | Wall mount                       |
| Operating Temperature | -5~45°C                          |
| Operating Humidity    | 5~90%                            |
| LED Indicator         | Yes                              |
| Static Consumption    | ≤0.01mw                          |
| Interface             | NC interface for extended sensor |
| Power Supply          | 1 Battery CR123A, 3V             |
| Activation Distance   | 2.5cm                            |
| Battery Life          | Up to 10 years                   |

#### Radio

| Radio Protocol           | CoSS |
|--------------------------|------|
| Signal Range(Open Field) | 800m |

#### Construction

| White/Black                 | White      |
|-----------------------------|------------|
| Sensor Dimension            | 22*22*89mm |
| Magnet Dimension            | 10*12*89mm |
| Casing                      | PC         |
| Net Weight (with battery)   | 44g        |
| Gross Weight (with battery) | 75g        |

#### Features

| Supports |
|----------|
| Supports |
| Supports |
| Supports |
| AES128   |
|          |



- ① Door/Window sensor
- ② Magnet
- ③ Indicator
- ④ Wall-mount bracket

- ⑤ External sensor input interface
- 6 Power on/off switch
- ⑦ Tamper protection button
- Screw hole

| Dimension<br>Contents | 120*70*35mm;<br>DEFED Door/Window Ser              |                         |                |                       |                                   |   |
|-----------------------|--|-------------------------|----------------|-----------------------|-----------------------------------|---|
| Contents              | DEEED Door/Window Ser                              |                         |                |                       |                                   |   |
|                       | 2 El EB 2 0 01, 1111001 001                        | nsor (with built-in bat | ttery) *1,     |                       |                                   |   |
| 1                     | User Guide *1, Screw Kit *<br>LifeSmart®<br>⊽orred | r1, 3M Adhesive *3      |                | VDERD<br>NSOR<br>NSOR | DEFED<br>DOOR<br>WINDOW<br>SENSOR | Bigger |
| EFED Door/Window Sens | or User Guide *1                                   | Screw Kit *1            | 3M Adhesive *3 |                       |                                   | 6 932046 202732 Made in China   |

Package

### DEFED Door/Window Sensor